


Revision Record


Revision	DCO	Description	Engineering Approval	Date	QA Approval	Date	Release Date
-		Initial Release	EJ	11/05/07	TM	11/05/07	11/05/07
A		Change micro mfg, 3.3.3.1. Table III.					10/6/08
B		Remove revision reference 2.1.					5/20/09
C		Change 3.3.3.1 for use of AC191, Table II max vcc, Table III for tr/ta.					9/19/12
D	5619	Change document format/number. Update microcircuit usage. Update Table 1, code H. Add typical jitter to Table 3, lcc.	CH RD	7/19/16 8/29/16	SD	8/15/16	8/29/16
E	6883	Add EAR Destination Statement; corrected freq. breakpoints in 6.4.3.1 & Table 2.	Curtis Hooper Richard Duong	6/19/17 6/21/17	Daniel Moline	6/27/17	6/29/17

This product and related technical data are subject to the EAR as promulgated and implemented by the U.S. Department of Commerce Bureau of Industry and Security. This product and related technical data are controlled under Export Control Classification Number (ECCN) 9A515.e.1 of the Commerce Control List (CCL), and may not be exported, re-exported, or re-transferred outside of the U.S. or released or disclosed to Foreign Persons, as defined by the EAR, without first complying with all applicable U.S. Export Regulations.



<p>UNLESS OTHERWISE SPECIFIED Dimensions are in Inches</p> <p style="text-align: center;"><u>Tolerances</u></p> <table border="0"> <tr> <td style="text-align: center;">Decimal</td> <td style="text-align: center;">Fraction</td> <td style="text-align: center;">Angular</td> </tr> <tr> <td style="text-align: center;">.xxx ± .005</td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">.xx ± .02</td> <td style="text-align: center;">$x/x \pm 1/16$</td> <td style="text-align: center;">$x^\circ \pm 2^\circ$</td> </tr> <tr> <td style="text-align: center;">.x ± .1</td> <td></td> <td></td> </tr> </table>	Decimal	Fraction	Angular	.xxx ± .005			.xx ± .02	$x/x \pm 1/16$	$x^\circ \pm 2^\circ$.x ± .1			<p>Proprietary Rights are involved in the subject matter of this material and all manufacturing, reproduction, use, and sales rights pertaining to such matter are expressly reserved. It is submitted in confidence for a specified purpose, and the recipient, by accepting this material, agrees that this material will not be used, copied, or reproduced in whole or in part, nor its contents revealed in any manner, or to any person, except for the purpose delivered.</p>
Decimal	Fraction	Angular											
.xxx ± .005													
.xx ± .02	$x/x \pm 1/16$	$x^\circ \pm 2^\circ$											
.x ± .1													

DETAIL PRODUCT SPECIFICATION CONTROL DRAWING

Initial Release			Q-Tech Corporation	
Prepared	Date		10150 West Jefferson Boulevard Culver City, CA 90232-3510 USA	
B. Remtulla	11/05/07		TITLE	
Checked	Date	HYBRID CRYSTAL OSCILLATOR, CLASS S, QT641C, DETAIL SPECIFICATION FOR		
E. Jackson	11/05/07			
Engineering Approval	Date	DRAWING NO. REVISION		
E. Jackson	11/05/07			
Quality Assurance Approval	Date	QPDS-0123		E
T. Mitchell	11/05/07	SCALE	SIZE	CAGE CODE
Released	Date	NONE	A	51774
T. Mitchell	11/05/07			1 of 6

1 PURPOSE

1.1 The purpose of this Detail Specification Control Drawing (SCD) is to describe the specific quality and reliability requirements for hybrid, hermetically sealed, crystal oscillators for use in space flight missions.

2 SCOPE

2.1 This specification establishes the minimum detail requirements for QT641C intended for use in conjunction with the applicable general SCD.

3 PART PROTECTION AND SAFETY

3.1 These items are susceptible to breakdown damage resulting from electrostatic discharge. Every precaution shall be taken while handling, installing, and testing the parts to prevent static charge. Care should be exercised to not apply more than rated voltage or current to any terminal/pad during testing.

4 PART NUMBER

4.1 The Q-Tech Part Number shall be as specified in Table 1 herein.

5 APPLICABLE DOCUMENTATION & REFERENCES

5.1 The following documents form a part of this drawing to the extent specified or modified herein.

5.2 **Q-Tech**

5.2.1 0401-00298-0001, Hybrid Crystal Oscillators, Class S, General Specification for

5.3 **Application of Documents**

5.3.1 **Issue of Documents**

Document revisions in effect on the date of the customer purchase order form a part of this drawing except as modified herein.

5.3.2 **Order of Precedence**

In the event of conflict between this document and the references cited herein or other requirements, the precedence in which requirements shall govern, in descending order, is as follows:


- a) Applicable Customer Purchase Order
- b) Applicable Q-Tech Corporation Detail SCD/Drawing
- c) Applicable Q-Tech Corporation General SCD
- d) Other Specifications, Standards, and Documentation Referenced Above

5.3.3 **Customer Purchase Order Special Requirements**

Additional special requirements shall be specified in the applicable customer purchase order when additional requirements or modifications are needed for compliance to special programs or product line compliance. Unique identification of the items produced may be required.

5.3.4 **General Specification Control Drawing**

Any reference to the “general specification” or “general SCD” refers to the Q-Tech Corporation General Specification Control Drawing cited in the Applicable Documentation and References section, unless otherwise specified.



6 GENERAL REQUIREMENTS

6.1 Definition of Requirements

Items supplied to this detail SCD shall meet the detail requirements specified herein.

6.2 Individual Item Requirements

The individual item requirements shall be in accordance with Q-Tech Corporation General SCD 0401-00298-0001 with the exceptions, modifications, and additions herein.

6.3 Approved Source of Supply

Hybrid crystal oscillators shall be supplied from the manufacturer specified in "Source of Supply" below.

6.4 Design and Construction

6.4.1 Outline Dimensions and Terminal Connections

The outline dimensions and terminal connections shall be as shown in Figure 1 herein.

6.4.2 Package Body and Lead Finish

The package body and lead finish shall be gold in accordance with MIL-PRF-38534.

6.4.3 Active Devices

The microcircuit used in this part shall use CMOS technology and shall be from a wafer proven to be radiation tolerant to 100 KRad (Si) total ionizing dose.

6.4.3.1 CMOS Microcircuit Usage

For frequencies below 3.75 MHz, the CMOS output microcircuit shall be 54AC191, see DSCC SMD 5962-89749. For frequencies from 3.75 MHz but below 15 MHz, the CMOS output microcircuit shall be 54AC74, see DSCC SMD 5962-88520. For frequencies greater than or equal to 15 MHz, the CMOS microcircuit shall be 54AC00, see DSCC SMD 5962-87549. These microcircuits are specified to be single event latchup free for LET up to 93 MeV-cm²/mg. The manufacturer shall be ST Microelectronics Corporation.

6.5 Performance Requirements

6.5.1 Maximum Ratings

The maximum ratings shall be as specified in Table 2 herein.

6.5.2 Electrical Performance Characteristics and Limits

The electrical performance requirements and limits shall be in accordance with Table 3 herein.

6.5.3 Delta Limits

Except for frequency aging (refer to Table 3 herein), delta limits shall be in accordance with the general SCD.

6.5.4 Total Dose Radiation Limits

Hybrid crystal oscillators supplied in accordance with this detail SCD shall be capable of meeting the performance requirements after being exposed to 100 KRad (Si) total dose radiation levels.


7 QUALITY ASSURANCE PROVISIONS

7.1 General

The quality assurance provisions shall be in accordance with the general SCD with the exceptions, modifications, and additions specified herein.

7.2 Screening

The screening tests shall be in accordance with the general SCD.



7.3 Quality Conformance Inspection (QCI)

Quality Conformance Inspection shall be in accordance with the general SCD and shall be required only when specified by the purchase order.

8 PREPARATION FOR DELIVERY

8.1 Preservation, Packaging, and Packing

Hybrid crystal oscillators shall be prepared for delivery in accordance with the general SCD.

8.2 Electrostatic Discharge Sensitivity

The devices supplied to this detail SCD shall be considered to be electrostatic discharge sensitive and require further protection and shall use the packaging requirements class 1C in accordance with par. 3.9.5.8.2 of MIL-PRF-38534.

9 SOURCE OF SUPPLY

9.1 Approved Manufacturer

Q-Tech Corporation
10150 West Jefferson Boulevard
Culver City, CA 90232-3510 USA

10 NOTES

10.1 The notes of the general SCD are applicable to this drawing.

10.2 Ordering Information

The procuring activity shall advise Q-Tech Corporation at the time of Request for Quotation if quality conformance inspection is to be required.

Table 1 – Part Number

Model Number	Supply Voltage	Temperature Stability	Duty Cycle	Screening	Frequency (MHz)
QT641	C: 5.0	A: ±65 PPM, -55°C to +125°C	1: 60/40	E: Engineering Model	1.000000 to 100.000000
		B: ±50 PPM, -55°C to +125°C	2: 45/55	M: Flight Model	
		C: ±50 PPM, -55°C to +105°C			
		D: ±40 PPM, -55°C to +105°C			
		E: ±30 PPM, -40°C to +85°C			
		F: ± 50 PPM, -20°C to +70°C			
		G: ±25 PPM, -20°C to +70°C			
		* H: ±5 PPM, 0°C to +55°C			

* Frequency/Temperature stability (tolerance) shall be referenced to the specified nominal output frequency, except for temp code H, in which case it is referenced to room temperature (T = 25 ± 2 °C). For temp code H, room temperature tolerance shall be ± 15 PPM.

Part Number Examples

QT641CB2M-16.000000MHz would be a Flight Model QT641, CMOS, 5.0 volts, stability ±50 PPM over -55°C to +125°C, 45/55 duty cycle, @ 16MHz output.

QT641CE1E-100.000000MHz would be an Engineering Model QT641, CMOS, 5.0 volts, stability ±30 PPM over -40°C to +85°C, 60/40 duty cycle, @ 100MHz output.


	Q-Tech Corporation Detail Product Specification Control Drawing	SIZE A	CAGE CODE 51774	DRAWING NO. QPDS-0123	REVISION E	PAGE 4 of 6

Table 2 – Maximum Ratings


Parameter	Symbol	Minimum	Maximum	Units
Supply Voltage	V _{CC}	0	7	Volts
Operating Temperature	T _C	-55	+125	°C
Storage Temperature	T _{STG}	-65	+150	°C
Lead Solder Temperature/Time			+250/10	°C/Seconds
Package Thermal Resistance	Θ _{jc}		50	°C/W

Table 3 – Electrical Performance Characteristics

Electrical Parameter	Test Conditions (Note 2 and 3)	Limits				Notes
		Min.	Nom.	Max.	Units	
Frequency Range		0.9375		100	MHz	
Frequency/Temperature Stability		See Table 1				Note 1, 4
Supply Voltage		4.5	5	5.5	Vdc	
Input Current Measured without load at 5.5 Vdc	Output Frequency:					
	Below 60 MHz			25	mA	
	60 MHz – 100 MHz			45	mA	
Load			CMOS			Note 6
Output Voltage – Logic “0”				V _{CC} x 0.1	Vdc	
Output Voltage – Logic “1”		V _{CC} x 0.9			Vdc	
Output Waveform		Squarewave			N/A	
Rise / Fall Time	Output Frequency:					
	Less than 15 MHz			5	nsec	
	15 MHz - 80 MHz			4	nsec	Note 7
	> 80 MHz			3	nsec	Note 7
Duty Cycle	Option 1:	40	50	60	%	
	Option 2:	45	50	55	%	
Frequency Aging (After 30 Days)	70°C ± 3°C			±1.5	ppm	
Frequency Aging (After 1 Year)	70°C ± 3°C			±10	ppm	
Start Up Time				10	msec	
Jitter (cycle-to-cycle, rms)	Output Frequency:					
	Less than 3.75 MHz			40	ps	Note 8
	3.75 MHz – 100MHz			10	ps	Note 8

NOTES

1. The limit for Frequency Stability (tolerance) is referenced to the specified nominal output frequency, except for temp code H as noted above.
2. Unless otherwise specified, the limits are over the full operating temperature range, and under specified load conditions and nominal Supply Voltage.
3. Unless otherwise specified, all measurements are in accordance with MIL-PRF-55310.
4. Up to 30 days after shipment.
5. Voltage values are with respect to network ground terminal.
6. A standard CMOS load of 10 KΩ || 15 pF shall be used. See MIL-PRF-55310/26 for CMOS waveform measurement definitions.
7. Measured between 10% Vdc and 90% Vdc.
8. Guaranteed by design, not tested.






Figure 1 – Package Dimensions and Terminal Connections

Table 4 – Terminal Connections

Terminal No.	Connection	Terminal No.	Connection
1	N/C	8	OUTPUT
7	GROUND/CASE	14	Vcc

NOTES

1. Dimensions are in inches.
2. Lead numbers are for reference only and are not marked on the unit.
3. A triangle symbol is marked on the corner of the package to indicate Pin 1.

